

FO-POXY (EWP)

Rapid Set Emergency Wet Surface Repair Compound

DESCRIPTION : Rapid Setting thick Paste consistency compound, having excellent ability for repairing and rebuilding parts or pipelines under adverse damp conditions. It is ideally used for wet surface repairs.

APPLICATION : Repair of Steel or Concrete surfaces that are in wet conditions or in splash zone areas. Used in repairs of damaged vessel, pipes, pumps, Pilings and Drainage canals, ditches, drilling rigs, structural supports, radiator leakages and pipeline leakages under damp/wet conditions.

Also useful in repairing concrete and tiles under water viz. dams, swimming pools, fire water storage columns, etc.

<u>PROPERTIES</u> :	Pot Life	(mins)	- approx. 4 to 5 mins.
	Set Time	(mins)	- 8 to 10 minutes
	CURE TIME	(Hrs.)	- 2
	COMPRESSIVE STRENGTH	(KGS/CM ²)	- 400
	TENSILE SHEAR STRENGTH	(KGS/CM ²)	- 100
	FLEXURAL STRENGTH	(KGS/CM ²)	- 375
	HARDNESS	(SHORE D)	- 78

TEMP. RANGE : UPTO 100 °C

MIXING RATIO : Base : Curing Agent is 2 : 1 by weight.

CHEMICAL REACTIVITY : Doesn't react with common industrial gases, acids, reagents and solvents.

ADDITIONAL INFORMATION : Can be prepared as per client specification.
Coverage Area : 1200 sq.cm./Kg for 5 mm product thickness

MANUFACTURED BY :

AQUADRA FORSPEC PVT. LTD.

2-A, Tower A, Viceroy Park, Kandivli (E), Mumbai - 400 101

Tel : +91 9820 393 292 / +91 98209 90182

E-mail : aquadraforspec@gmail.com

URL : <http://www.aquadra.in>